

# ULTRA TEX

PRODUCT CODE: TTWMTD51UT

Markhor's Ultra Tex is ready mixed, breathable, ultra tough based on a tough, durable acrylic copolymer resin, pigmented with titanium dioxide and other light fast alkali resisting pigments. Its formulation incorporating fungicides and algacides. Exceptionally durable protection against even extreme weather conditions UV protection for long lasting colour Flexible film resists cracking and reduces maintenance costs.



## RECOMMENDED AREAS OF APPLICATION

**Area of use:** Exterior  
**Substrate:** Concrete, Plaster, Masonry, Brickwork, Block work, Gypsum

## TECHNICAL DATA

**Sheen Variants:** Texture White  
**Colours Volume:** As per Ultra and IC Matt Shade Cards  
**Solids:** 50 ± 2%  
**Specific Gravity:** 150 (Theoretical White)

<b>Film Thickness Calculation</b>		Vary on average	
<b>Spreading Rate</b>		Depends on film Thickness/Surface consistency/level, temperature etc.	
<b>Spreading Rate Average formula</b>		$\frac{\text{Spreading Rate (ft}^2\text{/kg or m}^2\text{/kg)}}{\text{Specific Gravity}}$	
<b>Practical Covering Capacity:</b>	For estimation of practical covering capacity, following factors to be taken into account: surface profile, uneven application, over spray, losses in container and equipment etc.		
<b>Drying time</b> (Related Humidity 50%)	<b>Substrate Temperature</b>	<b>Touch Dry</b>	<b>Overcoating Interval</b>
			<b>Minimum</b> <b>Maximum</b>
	25 °c	4 Hours	8 Hours
	35 °c	3 Hours	6 Hours
	45 °c	2 Hours	4 Hours
			Indefinite

**APPLICATION DATA**

**Method of application:** Knockdown knives, Trowels and suitable tools for application.  
**Thinner:** Sweet water  
**Thinning ratio (by vol.):** Use 5% to 10% for ease of application. Dilution with sweet water will make the textures smaller. Do not over dilute.

**SURFACE PREPARATION**

The performance of this coating is directly related to the degree of surface preparation

- Ensure surface is clean, dry and free from all contaminants.
- Surface must be sound and free from laitance.
- Remove laitance by wire brush or sweep blast.

*Note: Fungal growth should be treated with Fungicidal Solution. After drying, one coat of Ultra/ECO Primer should be applied*

**APPLICATIONS DETAILS**

- Ensure adequate ventilation during application and drying.
- Do not apply when humidity exceeds 85% and condensation is likely.
- Surface temperature should be 3°C or more above dew point.
- Stir the contents thoroughly before and during use, with a broad flat stirrer, using an upward lifting action.

TYPICAL PAINT SYSTEM	
Markhor's Ultra Primer	1 Coat
Markhor's Ultra Tex	2 Coats (Subject to Thickness)
Markhor's Ultra Matt	2 Coats or 1 Coat (If Glazing)
Arte Di Colore's Biva Glazer	1 Coat
For alternate system suggestion please contact Sales Representative or <b>+92 333 MARKHOR (6275467)</b>	

**OTHER DETAILS**

- Contents of packaging with different batch numbers must be mixed together before use.
- Other systems may be specified, depending on area of use.
- Masking tape has to be removed immediately after application of the topcoat.

**First-Aid**

- **Eyes:** In the event of accidental splashes, flush eyes immediately with warm water and obtain medical advice.
- **Skin:** Wash skin thoroughly with soap and water, or with an approved industrial cleaner. Do not use solvents.
- **Inhalation:** Move patient to fresh air, loosen collar and keep patient rested.
- **Ingestion:** Do not induce vomiting. Obtain immediate medical attention
- Dispose in landfill only.

### SAFETY INFORMATION AND PRECAUTIONS

- Stir well and strain before use.
- Clean up all equipment with water immediately after use.
- Make sure that products is out of reach of children and pets.
- Keep away from food and drinks.
- Product must always be stored in a cool and dry place.
- Product must always be stored in a cool and dry place.
- Leftover material should be sealed and stored in an area that will protect it from damage, freezing and temperatures above 95°F.
- Don't swallow it. (If swallowed, seek medical advice urgently).
- Don't breathe the vapor or sanding dust.
- Avoid contact with eyes and skin. May cause allergic skin reaction.
- When applying, it is advisable to wear eye protection. in case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
- Wear protective clothing and mask during application.
- Use soap and water to clean the paint splashes from skin.
- Care must be taken during transportation.
- Always keep container in a secure upright position
- Use sand to contain any spillage.
- Dispose of paint material in accordance with the appropriate environment International and Local regulations.
- Do not discharge into drains or environment.
- Chemical Safety Data Sheet available on request.
- Does not contain any added Lead, Mercury, Cadmium and Chromium compounds.

### DISCLAIMER

The information provided in this data sheet is not intended to be complete. It is the responsibility of the user to ensure that the product used is suitable for the purpose it is meant to serve. In view of various factors affecting the performance of the coating, we cannot assume responsibility for the product performance, nor do we accept any liability arising from use of this product, unless specifically agreed to in writing by us. The information provided in the data sheet may be modified by us without notice.